



ILD5

ILD5

DIODE—SHARP-CUTOFF PENTODE

GENERAL DATA

Electrical:

Filament, Coated:

Voltage. 1.4 dc volts

Current. 0.05 amp

Direct Interelectrode Capacitances:⁰

Pentode Unit:

Grid No.1 to Plate . . 0.18 μf

Input. 3.2 μf

Output 6.0 μf

⁰ With external shield connected to negative filament terminal.

Mechanical:

Mounting Position. Any

Maximum Overall Length 2-25/32"

Maximum Seated Length. 2-1/4"

Maximum Diameter 1-3/16"

Bulb T-9

Base Lock-in 8-Pin

Basing Designation for BOTTOM VIEW 6AX


Pin 1—Filament (+)

Pin 2—Pentode
Plate

Pin 3—Pentode
Grid No.2

Pin 4—Diode Plate

Pin 5—No
Connection



Pin 6—Pentode
Grid No.1

Pin 7—No
Connection

Pin 8—Filament (-),
Pentode
Grid No.3

Plug—Base Shell

PENTODE UNIT
AMPLIFIER—Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE. 110 max. volts

GRID-No.2 (SCREEN) VOLTAGE 50 max. volts

Typical Operation and Characteristics:

Plate Voltage. 45 90 . . volts

Grid-No.2 Voltage. 45 45 . . volts

Grid-No.1 Voltage. 0 0 . . volts

Plate Resistance (Approx.) 0.9 0.75 . megohm

Transconductance 550 575 . μmhos

Plate Current. 0.55 0.6 . ma

Grid-No.2 Current. 0.12 0.1 . ma

DIODE UNIT

The diode is located at the negative end of the filament and is independent of the pentode unit except for the common filament.